


NOTES:

- CONTRACTOR TO PROVIDE AND INSTALL GROUND ROD & COPPER WIRE.
- 2. THE GROUND ROD & #6 AWG CU BSD MUST BE INSTALLED DURING FOOTING INSTALLATION.
- 3. THE GROUND ROD MUST BE INSTALLED IN UNDISTRUBED SOIL AT LEAST 2" BELOW FINAL GRADE, PER NESC 215C.
- 4. CONTRACTOR TO COIL 3" OF COPPER WIRE AROUND TOP OF GROUND ROD, AND MAKE FINAL CONNECTIONS.
- 5. GROUNDING IS ACCOMPLISHED BY CONNECTING THE NEUTRAL CONDUCTOR (GREEN CONDUCTOR) TO THE GROUNDING CONDUCTOR NEAR THE POLE GROUNDING TAB.



Shared-Use Path	Lighting – Ground	Rod In	stal	latior	1
					<u> </u>

DRAWING NO:	RD-1335	DRAFTED BY: S. SHOP	S. SHORTES	REV	DATE	APPR
Divivino no:	110 1000	51011 125 511	3. 31101(123	1	06/21	ZJW
FILE NAME:	RD-1335.DWG	APPROVED BY:	Z. WEIGEL			
CCALE	NITC	EFFECTIVE DATE	C /4 O /2 O 24			
SCALE:	NTS	EFFECTIVE DATE:	6/10/2021			

