LUMINAIRE: PHILIPS HADCO URBAN WESTBROOK NON-FLARED (CXF14)

Series: CXF14

LEDs*: 32; 48; 64; 80

Generation: **G2** Finish: **A** Black

Optics*: 2 - Type II; 3 - Type 3; 4 - Type 4; 5 - Type 5

CCT: W 3000K

Voltage: A 120-277 VAC

Drive Current*: 3 - 350mA; 5 - 530mA; 7- 700mA

Optional Dimming*:

DA 4 Hrs 25% reduction; **DB** 4 Hrs 50% reduction; **DC** 4 Hrs 75% reduction; **DD** 6 Hrs 25% reduction; **DE** 6 Hrs 50% reduction; **DF** 6 Hrs 75% reduction; **DG** 8 Hrs 25% reduction; **DH** 8 Hrs 50% reduction; **DJ** 8 Hrs 75% reduction;

DALI Compatible with DALI; **N** No Dimming

Optional Programs:


1st Option: N No 1st Option

2nd Option: **CLO** Constant light output

3rd Option: **OTL** Over the life Surge Protection: **SP2** 20Vk/20kA

Luminaire Options: H House side shield

*to be determined by designer - see manufacture specifications



Shared-Use Path Lighting – Luminaire						
DRAWING NO:	RD-1345	DRAFTED BY:	S. SHORTES	REV	DATE	APPR
Divition no.	110 13 13	51011 125 511	3. 311011123	1	06/21	ZJW
FILE NAME:	RD-1345.DWG	APPROVED BY:	Z. WEIGEL			
CCALE	NITC	EFFECTIVE DATE	6/40/2024			
SCALE:	NTS	EFFECTIVE DATE:	6/10/2021			

