



GENERAL NOTES:

- 1. INFILTRATORS ARE APPLICABLE TO INFILTRATION OF NON-POLLUTION GENERATING SURFACES, SUCH AS RESIDENTIAL ROOFS. THEY ARE NOT INTENDED TO DIRECTLY INFILTRATE RUNOFF FROM POLLUTION GENERATING SURFACES, SUCH AS ROADS OR PARKING LOTS. INFILTRATORS DO NOT REQUIRE PRETREATMENT OR UIC REGISTRATION WHEN INFILTRATING ONLY RESIDENTIAL ROOF RUNOFF.
- 2. INFILTRATOR TESTING REQUIRED:
- -MINIMUM INFILTRATION RATE = 1.0 INCH PER HOUR
- 3. SETBACKS:
 - -INFILTRATORS MUST BE 10' FROM FOUNDATIONS AND 5' FROM PROPERTY LINES UNLESS APPROVED BY BUILDING OFFICIAL.

Infiltrator-Roof Drainage Only			CITY OF	
DRAWING NUMBER: ST-6070	DRAWN BY: SR	SCALE: N.T.S.	WILSONVILLE	
FILE NAME: ST-6070.DWG	APPROVED BY: NK	DATE: 10/8/14	PUBLIC WORKS STANDARDS	