

NOTES:

- 1. 3" COMPOUND METER (SUPPLIED BY CITY).
- 2. 3" FLG. D.I. SPOOL PIECE.
- 3. 3" DISMANTLING JOINT W/MECHANICAL RESTRAINT.
- 4. 3" FLG. RESILIENT SEATED GATE VALVE W/HANDWHEEL.
- 5. 3" FLG TEE & 3" BLIND FLANGE W/2" THREADED TAP (IP THREAD).
- 6. 2" BRASS ELBOW.
- 7. 2" BRASS PIPE
- 8. 2" BRASS F.I.P. X F.I.P. COUPLING AND 2" BRASS M.I.P. X 110 COMP. STRAIGHT COUPLING. MUELLER H-15428 OR FORD C847-Q.
- 9. 2" THREADED GATE VALVE W/HANDWHEEL. (IP THREAD).
- 10. 3 COATED "STAND-ON" PIPE SUPPORTS. SEE DETAIL NO. WT-3095.
- 11. OLD CASTLE 577LA (577-B BASE, 57-T-2-332P TOP, 352P FRAME AND DOOR). USE 352NS (NON-SLIP FINISH) FRAME AND DOOR IN AREAS WITH PEDESTRIAN OR BIKE FACILITIES.
- 12. 2" X 6" BRASS NIPPLE.
- 13. INSTALL STANDARD COMPOUND METER ASSEMBLY IN ACCORDANCE WITH DETAIL WT-3115.

3" Compound Meter			CITY OF	
DRAWING NUMBER: WT-3105	DRAWN BY: SR	SCALE: N.T.S.	WILSONVILLE	
FILE NAME: WT-3105.DWG	APPROVED BY: NK	DATE: 6/4/14	PUBLIC WORKS STANDARDS	